

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

Corteva Agriscience™ encourages you and expects you to read and understand the entire SDS as there is important information throughout the document. This SDS provides users with information relating to the protection of human health and safety at the workplace, protection of the environment and supports emergency response. Product users and applicators should primarily refer to the product label attached to or accompanying the product container. This Safety Data Sheet adheres to the standards and regulatory requirements of Lithuania and may not meet the regulatory requirements in other countries.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : DASSOIL

Unique Formula Identifier (UFI) : F987-H0DR-K00Q-KJGP

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Agriculture use.

1.3 Details of the supplier of the safety data sheet

COMPANY IDENTIFICATION

Manufacturer/importer

Corteva Agriscience Denmark A/S
Langebrogade 3H
DK – 1411 Copenhagen K
DENMARK

Customer Information Number : +45 45 28 08 00
E-mail address : SDS@corteva.com

Distributor / Supplier

Corteva Agriscience Lithuania UAB ; Spaces business center
Gedimino ave. 44A
1110 Vilnius
Lithuania

1.4 Emergency telephone number

SGS +32 3 575 55 55 OR

+370 5214 0490

Poison information center: 8-5 236 20 52

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2	H319: Causes serious eye irritation.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :

Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH401 To avoid risks to human health and the environment, comply with the instructions for use.

Precautionary statements : **Prevention:**
P280 Wear eye protection/ face protection.

Response:
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P391 Collect spillage.

Disposal:
P501 Remove the container in accordance with national legislation.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version 1.0 Revision Date: 03.04.2023 SDS Number: 800080003083 Date of last issue: -
Date of first issue: 03.04.2023

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. REACH Registration number	Classification	Concentration (% w/w)
Alkylphenol alkoxyolate	69029-39-6	Aquatic Chronic 2; H411	>= 90 - <= 100

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.
First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection).
- If inhaled : Move person to fresh air; if effects occur, consult a physician.
- In case of skin contact : Wash off with plenty of water.
- In case of eye contact : Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist.
Suitable emergency eye wash facility should be available in work area.
- If swallowed : No emergency medical treatment necessary.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No specific antidote.
Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Water spray

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

Alcohol-resistant foam

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Exposure to combustion products may be a hazard to health. Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Nitrogen oxides (NOx)
Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
Prevent from entering into soil, ditches, sewers, underwater.
See Section 12, Ecological Information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped,

Recovered material should be stored in a vented container. The vent must prevent the ingress of water as further reaction with spilled materials can take place which could lead to over-pressurization of the container.

Keep in suitable, closed containers for disposal.

Wipe up with absorbent material (e.g. cloth, fleece).

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

See Section 13, Disposal Considerations, for additional information.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Handle in accordance with good industrial hygiene and safety practice.
Smoking, eating and drinking should be prohibited in the application area.
Do not get in eyes.
Avoid contact with skin and eyes.
Avoid prolonged or repeated contact with skin.
Take care to prevent spills, waste and minimize release to the environment.
Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in a closed container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers. Store in accordance with the particular national regulations.

Advice on common storage : Strong oxidizing agents

Packaging material : Unsuitable material: None known.

7.3 Specific end use(s)

Specific use(s) : Plant protection products subject to Regulation (EC) No 1107/2009.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

Local exhaust ventilation may be necessary for some operations.

Personal protective equipment

Eye protection : Use chemical goggles.
Chemical goggles should be consistent with EN 166 or equivalent.

Hand protection

Remarks : Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur. Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Ethyl vinyl alcohol laminate ("EVAL"). Polyethylene. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 4 or higher (breakthrough time greater than 120 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 1 or higher (breakthrough time greater than 10 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

supplier.

Skin and body protection : Wear clean, body-covering clothing.

Respiratory protection : Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use an approved air-purifying respirator.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : Liquid.

Colour : Yellow to brown

Odour : Mild Phenolic

Melting point/range : Not applicable to liquids

Freezing point : 4 °C
Method: Literature

Boiling point/boiling range : Method: Literature
Decomposes before boiling

Upper explosion limit / Upper flammability limit : No test data available

Lower explosion limit / Lower flammability limit : No test data available

Flash point : ≥ 100 °C
Method: PMCC, closed cup

Auto-ignition temperature : 400 °C
Method: Literature

pH : 5,5 - 7,5
Method: ASTM E70
(10% aqueous solution)

Solubility(ies)
Water solubility : Method: Literature
Miscible in all proportions

Vapour pressure : 1,7 hPa
Method: Literature

Density : 1,022 g/cm³ (20 °C)
Method: Test method in development

Relative vapour density : No test data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

9.2 Other information

Explosives	:	Not explosive
Oxidizing properties	:	No
Evaporation rate	:	No test data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

No decomposition if stored and applied as directed.
Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Stable under recommended storage conditions. No hazards to be specially mentioned. None known.
---------------------	---	--

10.4 Conditions to avoid

Conditions to avoid	:	None known.
---------------------	---	-------------

10.5 Incompatible materials

Materials to avoid	:	Strong acids Strong bases
--------------------	---	------------------------------

10.6 Hazardous decomposition products

Carbon oxides

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Components:

Alkylphenol alkoxyate:

Acute oral toxicity	:	LD50 (Rat): > 5.000 mg/kg
Acute dermal toxicity	:	LD50 (Rabbit, male and female): > 2.000 mg/kg

Skin corrosion/irritation

Components:

Alkylphenol alkoxyate:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version 1.0 Revision Date: 03.04.2023 SDS Number: 800080003083 Date of last issue: -
Date of first issue: 03.04.2023

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Product:

Result : Eye irritation

Components:

Alkylphenol alkoxyolate:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitisation

Components:

Alkylphenol alkoxyolate:

Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Components:

Alkylphenol alkoxyolate:

Germ cell mutagenicity- Assessment : In vitro genetic toxicity studies were negative.

Reproductive toxicity

Components:

Alkylphenol alkoxyolate:

Reproductive toxicity - Assessment : In animal studies, did not interfere with reproduction., In animal studies, did not interfere with fertility.
Did not cause birth defects or any other fetal effects in laboratory animals.

STOT - single exposure

Product:

Assessment : Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Components:

Alkylphenol alkoxyolate:

Assessment : Evaluation of available data suggests that this material is not an STOT-SE toxicant.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

STOT - repeated exposure

Product:

Assessment : Evaluation of available data suggests that this material is not an STOT-RE toxicant.

Repeated dose toxicity

Components:

Alkylphenol alkoxyate:

Remarks : In animals, effects have been reported on the following organs:
Kidney.
Liver.

Aspiration toxicity

Product:

Based on physical properties, not likely to be an aspiration hazard.

Components:

Alkylphenol alkoxyate:

Based on physical properties, not likely to be an aspiration hazard.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Components:

Alkylphenol alkoxyate:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 4,8 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203 or Equivalent

LC50 (Oncorhynchus mykiss (rainbow trout)): 3,7 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203 or Equivalent

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 10,5 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202 or Equivalent

Toxicity to terrestrial organisms : dietary LC50: > 105 micrograms/bee
Exposure time: 2 d
Species: Apis mellifera (bees)

contact LD50: > 100 micrograms/bee
Exposure time: 2 d
Species: Apis mellifera (bees)

No Observed Effects Level (NOEL): 2.250 mg/kg
Species: Colinus virginianus (Bobwhite quail)

oral LD50: > 2.250 mg/kg
Species: Colinus virginianus (Bobwhite quail)

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Alkylphenol alkoxyate:

Biodegradability : Result: Not biodegradable
Remarks: Biodegradation under aerobic laboratory conditions is below detectable limits (BOD20 or BOD28/ThOD < 2.5%). Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

Chemical Oxygen Demand (COD) : 1,78 kg/kg

ThOD : 2,35 kg/kg

12.3 Bioaccumulative potential

Components:

Alkylphenol alkoxyate:

Partition coefficient: n- : Remarks: No bioconcentration is expected because of the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

If the material as supplied becomes a waste, follow all applicable regional, national and local laws.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 3082
RID	:	UN 3082
IMDG	:	UN 3082
IATA	:	UN 3082

14.2 UN proper shipping name

ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alkylphenol alkoxyate)
RID	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alkylphenol alkoxyate)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Alkylphenol alkoxyate)
IATA	:	Environmentally hazardous substance, liquid, n.o.s. (Alkylphenol alkoxyate)

14.3 Transport hazard class(es)

ADR	:	9
RID	:	9
IMDG	:	9
IATA	:	9

14.4 Packing group

ADR		
Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9
Tunnel restriction code	:	(-)
RID		
Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9
IMDG		
Packing group	:	III
Labels	:	9

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

EmS Code : F-A, S-F
Remarks : Stowage category A

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

Marine Pollutants assigned UN number 3077 and 3082 in single or combination packaging containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 KG or less for solids may be transported as non-dangerous goods as provided in section 2.10.2.7 of IMDG code, IATA Special provision A197, and ADR/RID special provision 375.

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. E2 ENVIRONMENTAL HAZARDS

15.2 Chemical safety assessment

A Chemical Safety Assessment is not required for this substance when it is used in the specified applications.

The mixture is evaluated within the frame of the provisions of Regulation (EC) No. 1107/2009. Refer to the label for exposure assessment information.

SECTION 16: Other information

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

Full text of H-Statements

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



DASSOIL

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	03.04.2023	800080003083	Date of first issue: 03.04.2023

Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Eye Irrit. 2	H319
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

LT / 6N